


# Mars Lift and Tramway

Components of Omaha Trail,  
a system for high-efficiency transport between Earth and Mars



constructed with independently valuable components

# Omaha Trail, Components

## 1. Local Enhanced Terraforming:

- MATT: The Mars Terraformer Transfer
  - Omaha Crater: Cargo & Propellant
- => More at [lakematthew.com](http://lakematthew.com)!

## 2. Deimos Infrastructure:

- Deimos Dock
  - Deimos Rail Launcher (DRL)
- => More in our SEC 2017 presentation at [lakematthew.com](http://lakematthew.com)

## 3. Elevator-type Components:

- Mars Lift
- Tramway

## Overarching Goals:

Reduction of Earth Launches -> Lower Transport Costs  
Faster Transit Times -> Less Radiation Exposure  
Reduction of Resource Use on Mars  
Mid-Term Mars Settlement

Terraformation

# Omaha Trail, Terraforming

## Omaha Trail, Components

### 1. Local Enhanced Terraforming:

- MATT: The Mars Terraformer Transfer
- Omaha Crater: Cargo & Propellant

### 2. Deimos Infrastructure:

- Deimos Dock
- Deimos Rail Launcher (DRL)

=> More in our SEC 2017 presentation at [lakemattthew.com](http://lakemattthew.com)

### 3. Elevator-type Components:

- Mars Lift
- Tramway

### • Self-Sufficiency:

- Breathing and propellant gases, treated water and brine, hydroponics and food, most construction materials
- **in situ resource utilization (ISRU) => ~90% cut in cargo**

Terraformation

# Omaha Trail, Deimos Infrastructure

## 1. Local Enhanced Terraforming:

- MATT: The Mars Terraformer Transfer
- Omaha Crater: Cargo & Propellant

## 2. Deimos Infrastructure:

- Deimos Dock
- Deimos Rail Launcher (DRL)

## 3. Elevator-type Components:


- Mars Lift

### • Deimos Dock:

- Power (PV)
- **Volatiles** (Deimos density 1.5 g/cm<sup>3</sup>, Murchie et al. 2013, South Pole Mining, 50%wt volat., Fanale and Salvail 1990, CAVoR, Nichols 1993)
- **Construction Materials for Deimos Infrastructure, Tether, and Counterweight of Mars Lift**
- **Outside (most) of the Mars Gravity Well**
- **Propellant Replenishing off the Mars Surface for Mars Round-Trip**
- **4x PV compared to Mars Surface due to 4x Cumulative Solar**
- **Proving Ground for Technology**
- **Support for Construction and Operation of Mars Lift Drop Line**

### • Deimos Rail Launcher:

- **Boost without Propellant to Mars/Earth/Top of Elevator (1km/s  $\Delta v$ )**
- **Speed-up and Propellant-Savings, e.g., for Mars-Earth Transfer**
- **Most efficient conversion of PV power to  $\Delta v$**
- **Combined option for Mars EDL and Earth return with decision point at Mars periaopsis.**
- **Helical-coil EM launcher concept.**
- **Potential for acceleration and deceleration**
- **Potential for lightweight tether frame structure.**
- **300 MW HVDC ~600 GJ during launch, superconducting magnetic energy storage (SMES) for extra 2.8 TJ**
- **Gentle acceleration, e.g., 0.5 m/s<sup>2</sup> over 1000km rollout.**



Lake Matthew Team / Celestia



### 3. Elevator-type Components: Mars Lift Tramway

- **Value:**

- **Space Elevators and Tramways follow the Railway Paradigm:**
  - Invest in infrastructure, reap benefits from it.
- **Case for a Mars Space Elevator**
  - Drastically cut propellant requirements compared to landing rockets on the planet and taking off again for faster buildup of Mars infrastructure.
  - Lighter demands than Earth due to the Mars-Moons System promising a lighter feasibility condition.
- **Mars Lift**
  - Reduced requirements for an architecture as close as possible to implementation.
  - One way going down to start, effective drop-line compared to propulsive landing.
- **Tramway**
  - Railway equivalent with low requirements: low number of pylons and high tension elevator cable.

# Boundary Conditions for Mars Lift




## Plus

1. Lower gravity of Mars ( $\sim 1/3$  Earth) and similar rotation speed ( $\omega$ )  
=> **better for elevators than Earth**
2. Moons, with elevators

## Minus

1. Moons, to avoid
2. Dust storms up to 80 km altitude  $\Leftrightarrow$  Not even the highest peaks avoid them (Clancy, 2008)
3. Static electricity in the Martian atmosphere  $\Leftrightarrow$   $\sim 2$  orders of magnitude higher conductivity than Earth. Frequent discharges (dry lightning, dust devils, electrostatic dust). (Simoes et al. 2008; Aplin, et al. 2011)
4. Remote environment  $\Leftrightarrow$  Everything has to be brought in at first. In situ resource utilization (ISRU) is imperative for the whole Mars Lift concept.



Dust Devils with Glowing Tops, Mars Global Surveyor/Malin Space Science Systems, 2010

## and the Elevator Feasibility Condition






# Mars and Moons

## Phobos



## Deimos




- km from Mars center (above surface)
  - 9380 (5840)
  - 23436 (~20100)
- Orbit period:
  - 27600 s
  - 109000 s
  - (Mars days) 0.319
  - 1.262
- Projected speed over ground:
  - 1920 km/h
  - 162 km/h (retrograde)
- Mass:
  - $1.072 \cdot 10^{16}$  kg
  - $1.5 \cdot 10^{15}$  kg
- Radius:
  - 11.1 km
  - 6.2 km
- Mars radius: 3396 km
- Areostationary Orbit, km from Mars center (above surface): 20427 (17031)

# Options for Mars Lift

## 1. Use the Moons

- Phobos Tethers
  - Drop Tether of ~5740 km to avoid Mars atmosphere
  - Phobos Elevators L1, L2
- Deimos Tethers
  - Deimos Elevators, L1, L2



(Penzo, P. , July 1984)

## 2. Avoid the Moons

- Oscillations (Fountains of Paradise, 25. Orbital Roulette, Clarke)
    - Continual energy input required
    - Another degree of freedom that can be used as necessary
  - Off-Equator Mars Lift to avoid the moons
    - (compare Earth/general framework, Gassend 2004; Levin/Pearson 2005)
    - “Elevated ground state”
1. Use mountains (Olympus Mons, etc.) to avoid dust
  2. Do not use mountains



# Conclusions: Elevators for Mars Lift

## • Phobos Drop Tether

- + Avoids dust storms and electrostatic charge of the Mars atmosphere
- + Is the shortest possible tether of only ~6000 km
- 100 km vertical remain to be bridged
- Terminal velocity in Mars atmosphere is ~1000 km/h
- Even taking the lateral 1920 km/h of Phobos out with some other constructs, the vertical fall is hard to brake
- Braking a 100 km fall
  - Mars atmosphere: ~600 Pa, 0.6% of Earth. There will be no hypersonic aerodynamic Mars cargo planes!
  - Adding a parachute for 10 mt to every container or similar seems impractical (20m diameter supersonic parachute for 1 mt load for curiosity rover!)
  - Rockets burn propellant, which we are trying to avoid. ~3 mt per 10 mt cargo container, prohibitive
  - Infrastructure to brake the containers from the ground would be huge and therefore appears also prohibitive

⇒ **Mars atmosphere is just dense enough to be annoying but not useful**


⇒ **Drop tether economics appears undesirable**

## • Ground Tether, has to be

- robust against dust or requires a cleaning mechanism
- protected against electric discharge
- clear of the moons, therefore needs to be deployed off the equator
- almost ~20000 km long (or longer, clearing Deimos)

⇒ **Conclusion: Ground Tether further Investigated**

(Scenarios different than NIAC phase II study, p45, Edwards)







# Mars Lift, Feasibility Condition

New Version/Mars of the feasibility condition (work in progress):

1. The usual “leaky integrator” equation for the constructed/decaying tether that needs to be regularly serviced to remain in operation.
2. Moves from sums to factors where possible, stronger optimization criterion.
3. Includes a Geometry Condition: Irrespective of tether strength, a minimal tether size/surface area needs to be provided for climbers/rappellers to operate.
4. No Capstaning (wrapping around the wheels) for vehicles on Space Elevators
5. For Mars Lift, the direction is down and no climber motors or (almost no) power sources are necessary. Service/material comes from Deimos.





# Candidate Anchor Site 1, Elevator Peak

- Elevator Peak
  - ~ 6200 m Elevation
  - 18 S, 59.5 W





# Candidate Anchor Site 2, Pinnacle Station

- Morava Valles
  - ~ -2000 m
  - 12.65 S, 23.6 W





# Mars Lift, Tether Strength and Taper

- Specific Strength in MYuri is the relevant variable for Space Elevators
  - MYuri is a derived unit equal to N/tex (with tex = g/km) and GPa/(g/cm<sup>3</sup>) or 10<sup>6</sup> Nm/kg = 10<sup>6</sup> m<sup>2</sup>/s<sup>2</sup>
  - We assume a specific mass of CNTs of  $\rho=1.5$  g/cm<sup>3</sup> (values 1.3 – 2 are common)
  - Investigated are typically two tether strengths  $\sigma_0$  of:
    - 10 GPa => 6.6 MYuri
    - 20 GPa => 13.3 MYuri
  - Potential composed of gravitational pull, dependent on the distance from the center of gravity, and centrifugal force, dependent on distance from the rotation axis
 

$$V = -V_0 \left( \frac{r_s}{r} + \frac{1}{2} \frac{r_{\perp}^2}{r_s^2} \right)$$

$$\text{with } V_{0 \text{ Mars}} \approx 2.097 \text{ km}^2/\text{s}^2$$
  - and the relationship between tether cross section on the ground and the maximum at the aerostatic orbit is:
 

$$\frac{T}{T_0} = \frac{A}{A_0} = e^{\frac{\rho}{\sigma_0} \Delta V}$$
- Taper factors
  - 10 GPa tether: 4.15 (just tether, no loads) **with  $A_0 = 50 \text{ mm}^2$  (10x safety factor for 20 GPa) =>**
  - 20 GPa tether: 2.03 (just tether, no loads) **bracket for Tether Mass: ~1700 mt**




# Mars Lift, Curvature, Elevator Peak



$$\frac{d^2 \vec{r}}{ds^2} = -\alpha \left( \vec{g}(\vec{r}) \right)_\perp$$

- The curvature follows the tether shape equation
- Curvatures for 10 GPa and 20 GPa tethers anchored at 18° latitude for Elevator Peak:




- Clearance of moving Phobos orbit requires at least 185 km from the equator at Phobos orbit (brown ellipse) (1.12° latitude, Jacobson/Lainey, 2014)
- Presented are first approximative results. Shape will slightly change. Units of plot are in fraction of areosynchronous Orbit Radius (compare Gassend, 2004)
- Tether angles off the vertical ~28° (20 GPa) and ~40.7° (10 GPa)
- Payload goes with the Cos of tether angle!



# Mars Lift, Curvature, Pinnacle Station

- Lower latitude of  $12.65^\circ$  vs.  $18^\circ \Rightarrow$  less curvature of the elevator  $\Rightarrow$  tether angles:  $\sim 20^\circ$  (20 GP) and  $\sim 28.5^\circ$  (10 Gpa)
- Still clears Phobos orbit comfortably by a factor of  $\sim 1.8$  of the orbit change in this first calculation.
- If dust is tolerable, the lower latitude site offers integration advantages for the Omaha Trail.





# Mars Lift, Counterweight

- The safest option appears to terminate Mars Lift inside the Deimos orbit, e.g., at ~23000 km radius, put the top Ares station at ~400-500 km inside Deimos orbit.
- Bracketing the counterweight mass preliminarily for this situation:
  - The gradient of the combined potential of gravity and centrifugal force leads to
 
$$\vec{\nabla} V (60000 \text{ mt}, 23000 \text{ km}) \approx 2 \cdot 10^6 \text{ N}$$
  - A 20 GPa tether has at areostationary Orbit approximately that strength and that counterweight condition should not be exceeded.
- The Geometry Condition leads to a relatively strong elevator, variations of the counterweight mass scenario are still investigated.
- Putting the counterweight mass further out, e.g., past Deimos, will help to reduce the counterweight mass if necessary.
- Keep Ares Station close to Deimos for efficient transfers.




# Mars Lift, Deployment and Anchor Forces

- Expected is a ground force of up to  $10^6$  N for a functional elevator and to pull it into place for deployment.
- A large tractor (e.g., group of tanks) will have to pull the elevator to position or it will have to be deployed in its lightest form (TBD) and to be built up.
- How can an off equator configuration be kept stable while the elevator is built up, including building the counterweight?
- It is an advantage that the counterweight mass can be iteratively increased by transporting material from Deimos.
- **It is easier to build from above.**


# Mars Lift Rapeller

- **Rappeller** heat management:

- Brakes must counter gravitational acceleration
- Friction brakes would quickly overheat
- Eddy current brakes can work, but radiators are required



Lake Matthew Team



- Rappeller design considerations:

- Unpowered descent for cargo delivery
- Should be a mass-produced vehicle, easily repaired at Omaha Crater
- Lightweight, with compact storage
- Notional 10-ton payload (5 tons x 2)

Lake Matthew Team



# Tramway

- Conceptual design in the spirit of lunar tramway (Pearson et al. 2005)
- The rappeller designed to convert into HVDC “**trammer**”
- ISRU alloy pylons
- 30+ km pylon separation, peak-spanning, 400+ m pylon height
- CNT cables with Omaha Crater HVDC power
- Notionally 10x60 mm<sup>2</sup> cable cross-section with 70 kN tensioning






Figure 9. Lunar Space Elevator and Tramway




# Mars Lift and Tramway, Summary

- A simplified feasibility condition using rappellers and only going down, no large power source required.
- Empty trammers are folded up and recycled to Deimos/Mars Lift Top via rocket.
- The energy gained going down could possibly be used to build up (e.g., fuse new material to) or protect (e.g., clean/sweep) the Mars Lift elevator.
- To Do:
  - Look for further minimization of Elevator requirements
  - Investigate ideas for elevator protection and growth
  - Investigate deployment scenarios





# Thank you!



Lake Matthew Team / Celestia



# References I

**Disclaimer:** All presented Omaha Trail results are first approximations and may undergo corrections without notice.

- LakeMatthew.com
- Most astrodynamics data via Wolfram system (Mathematica, etc.)
- nasa.gov
- Background artwork: Kees Veenenbos, [www.space4case.com](http://www.space4case.com) and data: MOLA Science Team (NASA)
- MarsTrek site, JPL
- Google Earth, Mars Maps
- Tethers for Mars Space Operations. The Case for Mars II. 62 Science and Technology Series. pp. 445–465, Penzo, July 1984.
- Non-Equatorial Uniform-Stress Space Elevators, Gassend, 2004, including presentation on Off-equator space elevators and C code.
- Lunar Frontier Transportat System, Pearson et al., 2007
- Lunar Tether Transport, Levin, in Lunar Space Elevators for Cislunar Space Development, Pearson, 2005
- High Altitude Dust Global Distribution, Vertical Mixing, and Particle Sizes During the 2001 Planet-Encircling Dust Storm, Clancy, 2008
- Measuring Martian lightning, Aplin et al, 2011
- The Schumann resonance: A tool for exploring the atmospheric environment and the subsurface of the planets and their satellites, Simoes et al, 2008
- Martian satellite orbits and ephemerides, Jacobson/Lainey, 2014

# References II

- Aguayo, E., Kouzes, R. T., Ankney, A. S., Orrell, J. L., Berguson, T. J., & Troy, M. D. (2011). Cosmic ray interactions in shielding materials. *Pacific Northwest National Laboratory Report No. PNNL-20693*.
- Davis, A. M. (Ed.). (2005). *Meteorites, Comets, and Planets: Treatise on Geochemistry* (Vol. 1). Elsevier.
- D'Orazio, M., & Folco, L. (2003). Chemical Analysis of Iron Meteorites by Inductively Coupled Plasma-Mass Spectrometry. *Geostandards and Geoanalytical Research*, 27(3), 215-225.
- Engel, T. G., Timpson, E. J., & Veracka, M. J. (2015). Demonstration of a reversible helical electromagnetic launcher and its use as an electronically programmable mechanical shock tester. *IEEE Transactions on Plasma Science*, 43(5), 1266-1270.
- Engel, T. (2004). *U.S. Patent No. 6,696,775*. Washington, DC: U.S. Patent and Trademark Office.
- Fanale, F. P., & Salvail, J. R. (1990). Evolution of the water regime of Phobos. *Icarus*, 88(2), 380-395.
- Gay, S. E. (2010). *Contactless magnetic brake for automotive applications* (Doctoral dissertation, Texas A & M University).
- Hoashi, M., Brooks, R. R., & Reeves, R. D. (1993). Palladium, platinum and ruthenium in iron meteorites and their taxonomic significance. *Chemical geology*, 106(3-4), 207-218.
- Hughes, G. B., Lubin, P., Bible, J., Bublitz, J., Arriola, J., Motta, C., ... & Wu, J. (2013). DE-STAR: phased-array laser technology for planetary defense and other scientific purposes.
- Lubin, P., Hughes, G. B., Eskenazi, M., Kosmo, K., Johansson, I. E., Griswold, J., ... & Riley, J. (2016). Directed energy missions for planetary defense. *Advances in Space Research*, 58(6), 1093-1116.
- Murchie, S. L., Fraeman, A. A., Arvidson, R. E., Rivkin, A. S., & Morris, R. V. (2013). Internal characteristics of Phobos and Deimos from spectral properties and density: relationship to landforms and comparison with asteroids.
- Nichols, C. R. (1993). Volatile products from carbonaceous asteroids. *Resources of near-earth space*, 543-568.
- Pearson, J., Levin, E., Oldson, J., & Wykes, H. (2005). Lunar space elevators for cislunar space development. *NASA Institute for Advanced Concepts Study Technical Report*, 7.
- Schwenzer SP, Abramov O, Allen CC, Clifford SM, Cockell CS, Filiberto J, Kring DA, Lasue J, McGovern PJ, Newsom HE, Treiman AH. "Puncturing Mars: How impact craters interact with the Martian cryosphere." *Earth and Planetary Science Letters*. 2012 Jun 15;335:9-17.
- Shen, J. J., Papanastassiou, D. A., & Wasserburg, G. J. (1996). Precise Re-Os determinations and systematics of iron meteorites. *Geochimica et Cosmochimica Acta*, 60(15), 2887-2900.





# Image Credits

Blair, Jonathan S. / National Geographic / Getty Images: Eden Project greenhouse, Cornwall, England

Celestia Software: Simulated imagery of Mars system

Celle, Ludovic: Mars illustration

Clark, Chuck: natural boundary mapping of Deimos

HiRISE / MRO / LPL (U. Arizona) / NASA: Deimos imagery

NASA / JPL-Caltech / Malin Space Science Systems: Mars imagery

Öner, Tayfun / USGS / Thomas, Peter: Deimos mappings and orthographic renderings

Pearson et al. 2005: Lunar Space Elevator and Tramway

Pioneer Astronautics: CAVoR visualization

SpaceX: ITS visualizations

SSL / ASU / P. Rubin / NASA / JPL-Caltech: 16 Psyche artist's concept

Toshiba / Chubu Electric: SMES unit

U.S. Navy: F-14 on catapult

Wood, Roy: Surprise Lake inside Aniakchak Caldera

Veenenbos, Kees: Olympos Mons rendering: [www.space4case.com](http://www.space4case.com), and Data: MOLA Science Team (NASA)



# Backup Slides

2017-11-07


Mars Lift and Tramway, Components of Omaha Trail  
BIS Space Elevator Day, Martin Lades and Lake Matthew Team





# Deimos ISRU

- Deimos density:  $1.5 \text{ g/cm}^3$  (Murchie et al. 2013)
- ~50 wt% volatiles, within 20-60 m of polar surface (Fanale and Salvail 1990)
- Products: oxygen, methane, treated water
- Methods: CAVoR, alternate coal gasification reactions (Nichols 1993)




HiRISE / MRO / LPL (U. Arizona) / NASA



# Deimos Dock

**North**



Lake Matthew Team / Tayfun Öner / USGS / Peter Thomas





# Cargo

Mars

Deimos

LEO

Earth


1

2

3

4

5



# Cargo


- Comparing with SpaceX 2017 baseline:
  - Propellant per ton of cargo delivered: cut **68%**
  - Number of Earth launches per mission: cut **71%**





# Crew

- Water shielding: a Deimos ISRU product




# Crew

Mars

Deimos

LEO

Earth



2017-11-07



# Crew

- Comparing with SpaceX 2017 baseline:
  - Propellant per ton of crew & cargo delivered: cut **65%**
  - Number of Earth launches per mission: cut **83%**



# Crew

- Comparing with SpaceX 2017 baseline:
  - Extra shielding against solar flare protons in transit:
    - Water blocks extra **90%** en route to Mars
    - Water blocks extra **95%+** en route to Earth
- Solar flares no longer require transit **storm shelter**
- Add subaqueous habs and magnetostatic ground-surface shielding, for end-to-end protection. Prospect: an **unlimited Mars career**, with no career-limiting radiation dose, over **decades** of Mars work.

